

Transportation Safety Division

# 3M™ Stamark™ A721 T

## Wet Reflective Removable Tape

Product Bulletin Series A721 T

May 2020

### 1 Description


3M™ Stamark™ A721 T Wet Reflective Temporary Removable Tape is highly reflective under both wet and dry conditions. Series A721 T tape is a conformable marking material intended for longitudinal line applications in highway construction works zones, where removability will be required. After the end of the work zone, the tape can be removed intact or in large pieces.

3M™ Stamark™ A721 T is available in yellow.

3M™ Stamark™ A721 T tape utilizes specially designed optics to provide dry and wet reflective performance. The tape consists of a patterned rubber and is coated with a pressure sensitive adhesive for easy, rapid application in temperatures above 10°C.

### 2 Product construction

3M™ Stamark™ Pavement Marking Tape 721T



### 3 Product features

- Highly retroreflective, wet and dry
- No use of heavy metal compounds within the product for coloring
- Provides continuous delineation, day and night
- Easy to apply by hand or by machine
- Durable for normal work zone life
- Coated with pressure sensitive adhesive (PSA)
- Road may be open to traffic immediately
- Easy to remove intact or large pieces
- Leaves no lasting marks
- Available in yellow color

### 4 Product Performance

3M™ Stamark™ A721 T fulfils the following classes of EN 1436 in used condition:

Q	S	R <sub>L</sub>	R <sub>w</sub>
<i>Q 3</i> ≥ 130 mcd	<i>S 1</i> ≥ 45 SRT	<i>R 5</i> ≥ 300 mcd	<i>RW 6</i> ≥ 150 mcd

Q class: Qd values (retroreflection in diffused light)

S class: Skid Resistance value

RL class: Coefficient of retroreflected luminance following 30 m geometry in dry conditions

RW class: Retroreflection under wet conditions

3M™ Stamark™ A721 T has minimum initial retroreflectance values listed in the following table. Values are measured in accordance with CEN Standard EN 1436 Annex B

	Yellow
Entrance Angle	1.24°
Observation Angle	2.29°
Retroreflected Luminance	300 mcd·m <sup>-2</sup> ·lx <sup>-1</sup>

#### Skid Resistance

The surface of the 3M™ Stamark™ A721 T provides a minimum initial skid resistance value of 55 SRT. Values are measured in accordance with CEN Standard EN 1436 Annex D.

## Removability

3M™ Stamark™ A721 T is removable from asphalt and concrete surfaces intact or in large pieces at temperatures above freezing without use of heat, solvents, grinding or sandblasting. Use the following procedure:

- Wear gloves and use a chisel-like tool to pry up the edge of the tape
- Pull the tape straight up at an angle of 90° to the pavement
- A small amount of heat may be used to help soften the adhesive when removing Stamark™ tape at cold weather conditions. Note: Burning is not recommended.

## 5 Application

All applications of 3M™ Stamark™ A721 T tape should be installed using the instructions in this Product Bulletin and the appropriate Information Folders for Overlay Applications.

Climatic conditions for Overlay applications:

- Air and Surface Temperatures: +10°C and rising
- Relative Air Humidity: < 80 %

General surface conditions:

- Clean and dry surface no rain 24 hours prior to the application
- Always use 3M™ Stamark™ Surface Preparation Adhesive P50
- Butt splices must be used. Do not overlay tape ends.
- Do not apply tape on longitudinal seams or joints

## 6 Product Performance References

3M™ Stamark™ A721 T has been homologated by independent Test institutions in Europe:

Bundesanstalt für Strassenwesen (BASt)

Approval No. 2018 1VF 01.17 (3M™ Stamark™ A721 T)

## 7 General Performance Consideration

Maximum durability of 3M™ Stamark™ A721 T will be realized when properly applied according to 3M recommendations provided in product bulletins and information folders. The durability of Series A721 T tape will depend on traffic conditions, snow removal practices, application techniques used, and pavement and atmospheric conditions at the time of application. Damage may be caused by heavy trucks, excessive encroachment (crossover), narrow lane width, unpaved shoulders, snow removal and ice control techniques, such as sanding. It is recommended that the customer thoroughly evaluate Series A721 T tapes under the conditions in the specified location before making large- scale applications. While experience has shown that, properly applied, these materials are highly effective traffic control devices, 3M makes no generalized durability claims.

## 8 Storage

Store 3M™ Stamark™ A721 T in a cool dry area - indoors. Use within 12 months after receipt.

## 9.1 Health and Safety Information

Read all health hazard, precautionary and first aid statements found in the Material Safety Data Sheet (MSDS), and/or product label of chemicals prior to handling or use.

## 9.2 Disclaimer

THE 3M WARRANTY IS MADE IN LIEU OF ALL OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE, OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING OR OF PERFORMANCE, CUSTOM OR USAGE OF TRADE.

## 9.3 Limitation of Liability

Except for the limited remedy stated above, and except where prohibited by law, 3M will not be liable for any loss or damage arising from the Signs or any 3M product, whether direct, indirect, special, incidental or consequential damages (including but not limited to lost profits, business or revenue in any way), regardless of the legal theory asserted including warranty, contract, negligence or strict liability.

## 10 Other Product Information

Always confirm that you have the most current version of the applicable product bulletin, information folder or other product information from 3M's Website at <http://www.mmm.com/tss>.

## 11 Guarantee /Liability

3M assumes no responsibility for any injury, loss or damage arising out of the use of a product that is not of our manufacture. Where reference is made in literature to a commercially available product, made by another manufacturer, it shall be the user's responsibility to ascertain the precautionary measures for its use outlined by the manufacturer. Prerequisite for the guarantee is that the tape was processed according the instruction of this and other related technical information folders

## 12 Literature References

For additional information on 3M™ Stamark™ Tapes, Application Instructions or 3M™ Application Equipment, refer to the following publications:

IF OV	Information Folder Overlay Application
IF PS-98	Information Folder Adhesive Spray Applicator PS-98
IF P50	Information Folder Surface Preparation Adhesive 3M™ Stamark™ P50
IF MTA2	Information Folder Manual Tape Applicator MTA-2
IF RTC-3	Information Folder Roller Tamper Cart RTC-3

### Important Notice to Purchaser

All statements, technical information and recommendations herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. All questions of warranty and liability relating to this product are governed by the terms of the sale subject where applicable to the prevailing law. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer.

Reliant for these product-information:

3M Deutschland GmbH  
Transportation Safety Division Laboratory  
Carl-Schurz-Str. 1  
41453 Neuss, Deutschland

3M™ and Stamark™ are registered trademarks of 3M Company. All other trademarks belong to their respective owners.

The use of trademarks and brand names in this product information is subject to the regulations applicable in the USA. These may differ from those in other countries.



**3M Deutschland GmbH**  
**Transportation Safety Division**  
Carl-Schurz-Straße 1  
41453 Neuss  
Tel: 02131/14 7475  
Fax: 02131/14 3200  
E-Mail: [Verkehrssicherheit@mmm.com](mailto:Verkehrssicherheit@mmm.com)  
[www.3M.de/verkehrssicherheit](http://www.3M.de/verkehrssicherheit)

**3M Österreich GmbH**  
**Transportation Safety Division**  
Euro Plaza, Gebäude J  
Kranichberggasse 4  
1120 Wien  
Tel: +43(0)1/86686-0  
Fax: +43(0)1/86686-242  
E-Mail : [verkehrssicherheit-at@mmm.com](mailto:verkehrssicherheit-at@mmm.com)  
[www.3m.com/at](http://www.3m.com/at)

**3M (Schweiz) GmbH**  
**Transportation Safety Division**  
Eggstrasse 93  
8803 Rüschlikon  
Tel : +41447249272  
Fax : +41447249450  
E-Mail: [verkehrssicherheit-ch@mmm.com](mailto:verkehrssicherheit-ch@mmm.com)  
[www.3m.com/ch/verkehrssicherheit](http://www.3m.com/ch/verkehrssicherheit)

Subject to modifications  
Product Bulletin Series A721 T  
05.2020

© 3M 2020. All rights reserved.